



VHF MARINE TRANSCEIVER

IC-M73EURO

Slim, Stylish, Powerful VHF with Professional Features



Last Call Voice Recording*

The last call voie recording function automatically saves the last incoming call for 1 minute. You can also start recording manually. You will not miss an important call.



Active Noise Cancelling Technology*

The built-in bidirectional active noise cancelling reduces background noise to up to 90% and improves both your transmitted voice and incoming call. You will hear better and clearer!



Bass Boost Function*

The signal processing technology emphasizes lowpitched sound to provide a rich bass sound for both transmit and receive signals.



700mW Loud Audio

The IC-M73EURO uses a BTL (bridge-tied load) amplifier that doubles the audio output. Its internal speaker delivers a loud 700mW audio output with clear sound even in noisy environments.



6W RF Output Power

The IC-M73EURO's 6 Watts*1 of transmit power will provide extended communication range for the user. A large capacity Lithium-Ion battery allows for 18 hours of operation, under normal conditions*2.

*1 1W for FRG version, *2 Typical operation with 5:5:90 duty ratio.



IPX8 Advanced Waterproofing

The IC-M73EURO continues to offer Icom's best waterproof protection. The radio has been tested to survive after being submersed in 1.5m (4.9ft) depth of water for 30 minutes. Use this radio in the rain, snow or any other severe weather conditions!



Slim, Hourglass Body, Wide Viewing Angle LCD

The IC-M73EURO has a stylish, ergonomic design. A durable and rugged body provides for user-friendly operation and long life. A wide viewing angle, high intensity LCD offers bright, easy to read characters.

* Basic version (no voice recorder, no noise canceller and no bass boost function) available for limited markets.



IC-M73EURO

Additional features

- AquaQuake[™] water draining function ejects water from the speaker grille with low frequency sound.
- Dual/Tri-Watch function for monitoring Channel 16 and/or call
- Battery indicator shows remaining battery power in 4 levels
- Favorite channel and tag scan functions
- Optional speaker-microphones, HM-167 and HM-202
- Rapid charger BC-210 supplied with the IC-M73EURO
- Auto power save function
- FA-S64V short antenna

SPECIFICATIONS

| GENERAL | |
|---|--|
| Frequency range Tx Rx | 156.000-161.450MHz 156.000-163.425MHz |
| Usable channel groups | INT, USA* channels (* Depending on version) |
| Type of emission | 16K0G3E (FM) |
| Current drain (at 7.4V DC) Tx 6W output Rx Max. audio (Int SP/Ext SP) | 1.5A 450mA/250mA |
| Operating temp. range | –15°C to +55°C |
| Antenna impedance | 50Ω (SMA) |
| Dimensions (W×H×D) (projections not included) | 52.5×125×30 mm |
| Weight (approx.) | 280g (With BP-245N) 320g (With BP-245N, FA-S64V, MB-103) |

Measurements made in accordance with EN301-178-2. All stated specifications are subject to change without notice or obligation.

| TRANSMITTER | |
|---------------------------|----------------------------------|
| Output power (Hi/Mid/Low) | 6W/3W/1W 1/0.5W (FRG version) |
| Max. frequency deviation | ±5.0kHz |
| Frequency stability | ±1.5kHz |
| Spurious emissions | 0.25µW |
| Adjacent channel power | 70dB |
| Audio harmonic distortion | Less than 10% (at 60% dev.) |
| Residual modulation | 40dB |

- Supplied accessories:
 Battery pack, BP-245N Rapid charger, BC-210
 AC adapter, BC-123SE* Antenna, FA-S59V or FA-S64V*
- Hand strap Belt clip, MB-103
- *Not supplied or may differ depending on version

| RECEIVER | |
|------------------------------|-------------------------------|
| Sensitivity (at 20dB SINAD) | –2dBµ emf typ. |
| Squelch sensitivity | -6dBµ emf typ. (at threshold) |
| Adjacent channel selectivity | 70dB |
| Spurious response | 70dB |
| Intermodulation | 68dB |
| Hum and noise | 40dB |
| Audio output power | (at 10% distortion, 8Ω load) |
| Internal speaker | 700mW typ. |
| External speaker | 200mW |
| | |

Applicable IP Rating

| Ingress Protection | Standard |
|--------------------|------------------------------|
| Water | IPX8 (Waterproof protection) |

OPTIONS

Some options may not be available in some countries. Please ask your dealer for details



1900mAh (min.), 2000mAh (typ.)







Charges up to six BP-245N in 2.5 hours (approx.). AD-129 is supplied with the BC-197, depending on version.









ANTENNAS FA-S64V: 115mm antenna. FA-S59V: 150mm antenna.

This device has not been approved by the appropriate authorities in each country. This device may not be sold or leased, or be offered for sale or lease, until approval has been obtained. All stated features, appearances, screen shots and specifications may be subject to change without notice. Icom, Icom Inc. and the Icom logo are registered trademarks of Icom Incorporated (Japan) in the United States, the United Kingdom, Germany, France, Spain, Russia and/or other countries. AQUAQUAKE is a trademark of Icom Inc. (Japan) in the United States. All other trademarks are the properties of their respective holders.

Icom Inc. 1-1-32, Kami-minami, Hirano-ku, Osaka 547-0003, Japan Phone: +81 (06) 6793 5302 Fax: +81 (06) 6793 0013 Icom America Inc.

2380 116th Avenue NE, Bellevue, WA 98004, U.S.A. Phone: +1 (425) 454-8155 Fax :+1 (425) 454-1509 Fax :+1 (425) 454-1509
E-mail : sales@icomamerica.com
URL : http://www.icomamerica.com

Icom Canada

Glenwood Centre #150-6165 Highway 17, Delta, B.C., V4K 588, Canada Phone : +1 (604) 952-4266 Fax : +1 (604) 952-0090 E-mail: info@icomcanada.com
URL: http://www.icomcanada.com

Icom Brazil

Rua Pernambuco, 353 - Sala 901 Belo Horizonte, M.G. 30130-150. Brazil Phone: +55 (31) 3582 8847 Fax: +55 (31) 3582 8987 E-mail: sales@icombrazil.com

Icom (Europe) GmbH

Communication Equipment Auf der Krautweide 24 Auf der Krautweide 24 65812 Bad Soden am Taunus, Germany Phone : +49 (6196) 76685-0 Fax : +49 (6196) 76685-50 E-mail : info@icomeurope.com URL : http://www.icomeurope.com

Icom Spain S.L.

Ctra. Rubi, No. 88 "Edificio Can Castanyer" Bajos A 08174, Sant Cugat del Valles, Barcelona, Spain Phone: +34 (93) 590 26 70 Fax : +34 (93) 589 04 46 E-mail: icom@icomspain.com

Icom Polska

81-850 Sopot, ul. 3 Maja 54, Poland Phone : +48 (58) 550 7135 Fax : +48 (58) 551 0484

URL: http://www.icomspain.com

Icom (UK) Ltd.

Blacksole House, Altira Park, Herne Bay, Kent, CT6 6GZ, U.K. Phone: +44 (0) 1227 741741 Fax : +44 (0) 1227 741742 E-mail : info@icomuk.co.uk
URL : http://www.icomuk.co.uk

Icom France s.a.s.

Zac de la Plaine, 1 Rue Brindejonc des Moulinais, BP 45804, 31505 Toulouse Cedex 5, France Phone : +33 (5) 61 36 03 03 Fax : +33 (5) 61 36 03 00 E-mail: icom@icom-france.com URL: http://www.icom-france.com

Icom (Australia) Pty. Ltd.

Unit 1 / 103 Garden Road. Clayton, VIC 3168 Australia Phone: +61 (03) 9549 7500 x :+61 (03) 9549 7505 mail:sales@icom.net.au URL : http://www.icom.net.au

Icom New Zealand

146A Harris Road, East Tamaki, Auckland, New Zealand Phone: +64 (09) 274 4062 Fax : +64 (09) 274 4708 E-mail : inquiries@icom.co.nz URL : http://www.icom.co.nz

Asia Icom Inc.

GF No. 68, Sec. 1 Cheng-Teh Road, Taipei, Taiwan, R.O.C. Phone: +886 (02) 2559 1899 Fax: +886 (02) 2559 1874 E-mail: sales@asia-icom.com URL: http://www.asia-icom.com

Your local distributor/dealer:

www.icom.co.jp/world

Count on us!